

APS- SPD PDU Power 19" Rack



ABOUT PRODUCT

The SPD PDU Power 19" is designed to protect equipment against power surges and electrical noise while providing a convenient combination of power outlets to suit most applications. A unique mounting system allows mounting in a range of modes to suit crowded racks. Even if no rack space exists, the units may be mounted externally on the front or rear of the rack. For horizontal mounting, the units require a single 1RU rack space for installation. For vertical mounting, the unit requires 3RU (132mm) of rack space. The unit may also be flush mounted to either side of a rack or cabinet.

MAIN FEATURES

- Unique mounting system
- Rigid steel case
- 22.5kA Surge Rating
- Category A, Class III device
- Designed perfectly for server racks
- Super Compact
- Reduces electrical noise
- Enhances product reliability
- Plug and Play connection
- 5 year warranty



Technical Specifications

Current Rating	10A total
Configuration	Single-phase, L/N/E.
Surge Protection Category	AS/NZS1768 Category B
Primary Protection Modes	L-N, L-E, and N-E
Secondary Protection Modes	L-N, L-E, and N-E
Surge Rating (8/20us L-N)	22.5kA
Let-through Voltage	< 700V@ 3kA
Overvoltage Withstand	300VRMS
Filter Type	Low Q/low C filter providing differential and common-mode filtering.
Attenuation	> 50dB above 1MHz.
Voltage Drop	Less than 3V at rated load.
Input Connection	Approved power cord with Australian 10A plug
Output Connections	Australian 3 pin 10A (x8).
Enclosure	Steel, powder coated, black.
Dimensions (Without Brackets)	441 x 120 x 44 mm (W x D x H)
Weight	1.2kg

